

GAS INSERTS





MADISON PARK 34

The Madison Park gas fireplace insert brings convenience and efficient heating to an existing wood-burning fireplace. Listed to fit zero-clearance factory-built and masonry fireplaces, the Madison Park gas insert turns your standard wood burning fireplace into a cost-effective heat source that displays a realistic gas fire for brilliant warmth and ambiance.

OVERVIEW

- ♦ Available in large, medium and small models to fit a wide range of fireplace sizes.
- ♦ Electronic ignition system with battery backup—still ignites and heats during a power outage.
- ♦ Outstanding heating efficiency for increased comfort and lower operating costs.
- ♦ Ceramic glass for optimum heat transfer and a protective screen*.
- ♦ Beautifully crafted high-definition ceramic fiber log set.
- ♦ State-of-the-art burn technology provides the warm glowing appearance of an authentic fire.
- ♦ Choose between several distinctive styles of accessory façades to match the look of your existing décor (required).
- ♦ Interior selections consist of black reflective porcelain or a variety of ceramic fiber liners (required).
- ♦ Mood enhancing interior illumination with six distinctive settings (large & medium models).
- ♦ Factory installed blower with six speed settings to fine tune your heating needs.
- ♦ Full-function remote control included (IPI/CPI, thermostat, flame height, blower, lighting).
- ♦ 20 year limited warranty.

*All applicable models comply with ANSI Z21.50/88 barrier requirements.

MADISON PARK 34



Madison Park shown with Decco façade and Buff Rustic brick.

BTU INPUT NG: 25,000 - 38,000

BTU INPUT LP: 27,000 - 35,500

HEATING CAPACITY: 500 – 2000 square feet

AFUE EFFICIENCY: 67% (NG) 73% (LP)

ENERGUIDE (P4) EFFICIENCY: 66% (NG) 68% (LP)

BLOWER: 150-CFM

REMOTE CONTROL: Standard

MADISON PARK 32

BTU INPUT NG: 23,000 - 34,000

BTU INPUT LP: 28,000 - 34,000

HEATING CAPACITY: 500 – 1,750 square feet

AFUE EFFICIENCY: 71% (NG) 74% (LP)

ENERGUIDE (P4) EFFICIENCY: 65% (NG) 70% (LP)

BLOWER: 150-CFM

REMOTE CONTROL: Standard

MADISON PARK 27

BTU INPUT NG: 21,000 - 30,000

BTU INPUT LP: 20,000 - 25,000

HEATING CAPACITY: 500 – 1,500 square feet

AFUE EFFICIENCY: 67% (NG) 70% (LP)

ENERGUIDE (P4) EFFICIENCY: 68% (NG) 71% (LP)

BLOWER: 150-CFM

REMOTE CONTROL: Standard

OPTIONS

FAÇADES

Choose a face style that's right for your home.



Full Face Façade



Santa Fe



Contemporary



Deco

DECORATIVE ACCENT TRIMS

(For use with Full Face Façade only)



Frontier



Highliner



Iron Rail

LINER




Red Rustic



Buff Rustic



Porcelain



Flat Black

REMOTE



The standard Total Comfort Remote uses an integrated thermostat to keep your room at just the right temperature.

MADISON PARK CD™



MADISON PARK CD 34

The Madison Park CD gas fireplace insert adds the convenience of gas with contemporary styling to an existing wood burning fireplace. Listed to fit small zero-clearance factory-built and masonry fireplaces, the Madison Park CD turns your standard wood burning fireplace into a stylish and convenient heat source that you control with the press of a button.

OVERVIEW

- ◆ Available in large, medium and small models to fit a wide range of fireplace sizes.
- ◆ Electronic ignition system with battery backup—still ignites and heats during a power outage.
- ◆ Outstanding heating efficiency for increased comfort and lower operating costs.
- ◆ Ceramic glass for optimum heat transfer and a protective screen*.
- ◆ State-of-the-art burn technology and glass floor media provide a stunning flame presentation.
- ◆ Choose between several distinctive styles of accessory façades to match the look of your existing décor (required).
- ◆ Interior selections consist of black reflective porcelain or a variety of ceramic fiber liners (required).
- ◆ Multiple glass media kits are available to achieve a customized finished appearance (required).
- ◆ Mood enhancing interior illumination with six distinctive settings (large & medium models).
- ◆ Factory installed blower with six speed settings to fine tune your heating needs.
- ◆ Full-function remote control included (IPI/CPI, thermostat, flame height, blower, lighting).
- ◆ 20 year limited warranty.

*All applicable models comply with ANSI Z21.50/88 barrier requirements.

MADISON PARK CD 34



Madison Park CD shown with Porcelain interior and Sunset glass media.

BTU INPUT NG: 25,000 - 38,000

BTU INPUT LP: 27,000 - 35,500

HEATING CAPACITY: 500 – 2000 square feet

AFUE EFFICIENCY: 68% (NG) 70% (LP)

ENERGUIDE (P4) EFFICIENCY: 66% (NG) 70% (LP)

BLOWER: 150-CFM

REMOTE CONTROL: Standard

MADISON PARK CD 32

BTU INPUT NG: 23,000 - 34,000

BTU INPUT LP: 28,000 - 34,000

HEATING CAPACITY: 500 – 1,750 square feet

AFUE EFFICIENCY: 72% (NG) 74% (LP)

ENERGUIDE (P4) EFFICIENCY: 67% (NG) 72% (LP)

BLOWER: 150-CFM

REMOTE CONTROL: Standard

MADISON PARK CD 27

BTU INPUT NG: 21,000 - 30,000

BTU INPUT LP: 20,000 - 25,00

HEATING CAPACITY: 500 – 1,500 square feet

AFUE EFFICIENCY: 67% (NG) 69% (LP)

ENERGUIDE (P4) EFFICIENCY: 66% (NG) 68% (LP)

BLOWER: 150-CFM

REMOTE CONTROL: Standard

OPTIONS

FAÇADES

Choose a face style that's right for your home.



Full Face Façade



Santa Fe



Contemporary



Deco

DECORATIVE ACCENT TRIMS

(For use with Full Face Façade only)



Frontier



Highliner



Iron Rail

LINER



Red Rustic



Buff Rustic



Porcelain



Flat Black

GLASS MEDIA



Midnight



Cloud



Sunset

REMOTE



The standard Total Comfort Remote uses an integrated thermostat to keep your room at just the right temperature.



RAVENNA 40

The Ravenna gas fireplace insert offers the convenience of gas, the look of a real wood fire and an efficient source of supplemental heat. Listed to fit most zero-clearance factory-built and masonry fireplaces, the Ravenna turns your standard fireplace into a cost-effective heat source and warm, beautiful gathering place.

OVERVIEW

- ♦ Available in a medium size to fit most common fireplace sizes.
- ♦ Electronic ignition models include a battery backup—still ignites and heats during a power outage.
- ♦ Outstanding heating efficiency for increased comfort and lower operating costs.
- ♦ Ceramic glass for optimum heat transfer and a protective screen*.
- ♦ Beautifully crafted high-definition ceramic fiber log set.
- ♦ State-of-the-art burn technology provides the warm glowing appearance of an authentic fire.
- ♦ Interior selection consists of a natural tan brick ceramic fiber liner (required).
- ♦ Factory installed blower with six speed settings to fine tune your heating needs.
- ♦ Full-function remote control included (IPI/CPI, thermostat, flame height, blower).
- ♦ 20 year limited warranty.

*All applicable models comply with ANSI Z21.50/88 barrier requirements.

RAVENNA 40



Ravenna 40 shown with Contemporary face and Tan Brick liner.

BTU INPUT NG: 28,000 - 40,000

BTU INPUT LP: 26,000 - 37,500

HEATING CAPACITY: 500 – 2000 square feet

ENERGUIDE (P4) EFFICIENCY: 67% (NG) 69% (LP)

BLOWER: 150-CFM

REMOTE CONTROL: Standard

RAVENNA 33

BTU INPUT NG: 24,000 - 33,000

BTU INPUT LP: 24,000 - 33,000

HEATING CAPACITY: 500 – 2000 square feet

ENERGUIDE (P4) EFFICIENCY: 66% (NG) 68% (LP)

BLOWER: 150-CFM

REMOTE CONTROL: Standard

OPTIONS

FACE STYLE & FINISH



Contemporary  Black

LINER



Tan Brick

SURROUND AND TRIM

Choose your surround and trim.



Standard surround



Trim

 Black

REMOTE



The standard Total Comfort Remote uses an integrated thermostat to keep your room at just the right temperature.



BELLEVUE 32

The Bellevue gas fireplace insert is an easy and cost-effective way to transform your existing wood fireplace into a modern heating appliance. Enjoy the heritage and heat of warming by the fire without the hassle of chopping wood or the expense of a complete fireplace overhaul.

OVERVIEW

- ♦ Available in medium and small models to fit a wide range of fireplace sizes.
- ♦ Electronic ignition system with battery backup—still ignites and heats during a power outage.
- ♦ Outstanding heating efficiency for increased comfort and lower operating costs.
- ♦ Ceramic glass for optimum heat transfer and a protective screen*.
- ♦ Beautifully crafted high-definition ceramic fiber log set.
- ♦ State-of-the-art burn technology provides the warm glowing appearance of an authentic fire.
- ♦ Choose from two full front façades that provide a clean finished appearance (required).
- ♦ Optional decorative accent trims available to match the look of your existing décor.
- ♦ Black interior creates a stark contrast for the yellow dancing flames.
- ♦ Factory installed blower with six speed settings to fine tune your heating needs.
- ♦ Optional hand-held and wall mounted remote controls available for all models.
- ♦ 20 year limited warranty.

*All applicable models comply with ANSI Z21.50/88 barrier requirements.

BELLEVUE 32



Bellevue 32 shown with Full Front Façade and Highliner Decorative Accent Trim.

BTU INPUT NG: 16,000 - 28,000

BTU INPUT LP: 14,000 - 25,000

HEATING CAPACITY: 500 – 1,800 square feet

AFUE EFFICIENCY: 70% (NG) 67% (LP)

ENERGUIDE (P4) EFFICIENCY: 57% (NG) 61% (LP)

BLOWER: 150-CFM

REMOTE CONTROL: Optional

BELLEVUE 27

BTU INPUT NG: 14,000 - 25,000

BTU INPUT LP: 16,200 - 22,500

HEATING CAPACITY: 450-1625 square feet

AFUE EFFICIENCY: 78% (NG) 75% (LP)

ENERGUIDE (P4) EFFICIENCY: 73% (NG) 73% (LP)

BLOWER: 150-CFM

WREMOTE CONTROL: Optional

OPTIONS

FULL FRONT FAÇADE



Standard

DECORATIVE ACCENT TRIMS



Frontier



Highliner




Iron Rail

REMOTES



SPECIFICATIONS



DIMENSIONS

		Madison Park 27	Madison Park CD 27	Madison Park 32	Madison Park CD 32	Madison Park 34	Madison Park CD 34	Ravenna 33/40	Bellevue 27	Bellevue 32
Width	Front	26-5/8"	26-5/8"	31-5/8"	31-5/8"	33-5/8"	33-5/8"	31-1/4"	26-5/8"	31-5/8"
	Back/Rear	16-3/4"	16-3/4"	21"	21"	23"	23"	17-5/8"	16-3/4"	21"
Height	Overall	17-7/8"	17-7/8"	19-3/8"	19-3/8"	23-7/8"	23-7/8"	19-3/8"	17-7/8"	19-3/8"
Depth	Overall	14-7/8"	14-7/8"	15-7/8"	15-7/8"	16-1/4"	16-1/4"	15-7/8"	14-7/8"	15-7/8"
To Centerline (CL) of 3" Flue Collar		8-3/16"	8-3/16"	9-3/4"	9-3/4"	10"	10"	13-3/8"	8-3/4"	9-3/4"

MINIMUM CLEARANCES TO COMBUSTIBLES

Hearth protection to be minimum of 3/8" thick non-combustible or equivalent, with a k factor of .84.

CLEARANCES

		Madison Park 27 & Madison Park CD 27	Madison Park 32 & Madison Park CD 32	Madison Park 34 & Madison Park CD 34	Ravenna 33	Ravenna 40	Bellevue 27	Bellevue 32
A	1-1/2" Top facing to bottom of appliance	32"	32"	36"	31-1/2"	35-1/2"	26-5/8"	31-5/8"
B	Side facing or side wall to center of glass	23"	25-7/8"	26-7/8"	25-1/2"	25-1/2"	16-3/4"	21"
C	6" Mantel to bottom of appliance	34"	32"	36"	39"	43"	17-7/8"	19-3/8"
D	Vertical distance from base of appliance to hearth extension	0" 4"	0" 10"	0" 10"	0" 2" 4"	0" 2" 4"	14-7/8"	15-7/8"
E	Minimum horizontal distance from front of appliance	10" 0"	2" 0"	2" 0"	13" 10" 0"	14" 10" 0"	8-3/4"	9-3/4"

SURROUND SIZING

	Madison Park™ 27 & Madison Park™ CD 27	Madison Park™ 32 & Madison Park™ CD 32	Madison Park™ 34 & Madison Park™ CD 34	Ravenna™ 33/40		Bellevue 27	Bellevue 32
Standard Surround 3-pc	26" H X 37" W	26" H X 41" W	31" H X 41" W	29" H X 41" W	Required Full Front Façade		
	26" H X 41" W	26" H X 46" W	31" H X 46" W	29" H X 48" W			
	30" H X 37" W	33" H X 41" W	34" H X 41" W	33" H X 41" W	Medium	26" H X 37" W	25" H X 41" W
	30" H X 41" W	33" H X 46" W	34" H X 46" W	33" H X 48" W	Large	30" H X 41" W	32" H X 46" W
Standard Surround 1-pc	N/A	N/A	N/A	29" H X 41" W	*Optional 4-sided Surround Backer- Able to Be Trimmed		
4 Sided - Able to be Trimmed	38" H X 46" W	38" H X 46" W	42" H X 46" W	N/A		38" H X 46" W	
Cast Surround	N/A	N/A	N/A	30" H X 45-1/2" W			

* The 4-Sided Surround is compatible for use with the medium size Full Front Façades (41" x 25"-Bellevue 32 Model & 26" x 37" for the Bellevue 27) but not the large size Full Front Façade.

FIREPLACE SIZING

	Madison Park™ 27 & Madison Park™ CD 27	Madison Park™ 32 & Madison Park™ CD 32	Madison Park™ 34 & Madison Park™ CD 34	Ravenna™ 33/40	Bellevue 27	Bellevue 32
Front Width	27"	32"	34"	31-1/2"	27"	32"
Height	18"	19-1/2"	24"	19-1/2"	18"	19-1/2"
Rear Width	17"	22"	24"	18"	17"	22"
Depth	15"	16"	16"	16"	15"	16"

SIDE-BY-SIDE COMPARISONS

	MADISON PARK	MADISON PARK CD	RAVENNA	BELLEVUE
Models	Large, Medium, Small	Large, Medium, Small	Medium	Medium, Small
Design Style	Traditional	Contemporary	Traditional	Traditional
Interior Media	Ceramic Fiber Log Set	Glass Pebbles	Ceramic Fiber Log Set	Ceramic Fiber Log Set
Glass Front	Ceramic	Ceramic	Ceramic	Ceramic
Protective Barrier	Included	Included	Included	Included
Interior Illumination	Included Large & Medium	Included Large & Medium	N/A	N/A
Ceramic Fiber & Black Reflective Interior Liners	Required (choose 1)	Required (choose 1)	Required (choose 1)	N/A
Surround Panels	Required (choose 1)	Required (choose 1)	Required (choose 1)	N/A
Front Façade	Required (choose 1)	Required (choose 1)	Required (choose 1)	Required (choose 1)
Decorative Trim	Optional	Optional	Optional	Optional
Standard Blower	150 CFM Variable Speed	150 CFM Variable Speed	150 CFM Variable Speed	150 CFM Variable Speed
Controls	Electronic	Electronic	Electronic	Electronic
Multi-Function Touch Remote Control	Included	Included	Included	N/A
Wireless Wall Mounted Control	N/A	N/A	N/A	Optional
Hand Held Remote Control	N/A	N/A	N/A	Optional
United States ANSI Listing	Z21.88 Heater Rated	Z21.88 Heater Rated	Z21.88 Heater Rated	Z21.88 Heater Rated
United States AFUE Rated	Yes	Yes	No	Yes
Canada CSA Listing	2.33 Heater Rated	2.33 Heater Rated	2.33 Heater Rated	2.33 Heater Rated
Canada EnerGuide Rated	Yes	Yes	Yes	Yes
Venting Configurations	3" Co-Linear	3" Co-Linear	3" Co-Linear	3" Co-Linear
Warranty	20 Year Limited	20 Year Limited	20 Year Limited	20 Year Limited



785738M 06/20

© 2020 Innovative Hearth Products

IRONSTRIKE.US.COM

